

P605UL Laser Projector

Datasheet



Super silent yet brilliantly versatile

Innovation grounded in the true needs of the user results in the P605UL, a laser projector that is so silent it goes unnoticed yet for the 6,000 ANSI lumen image projection, perfectly visible in brightly lit spaces. A new standard in silent operation, 19dB in Eco mode is quieter than the ticking of a watch and is unsurpassed by any other installation projector. With 4K@30Hz input processing, comprehensive connectivity and supporting WUXGA resolution, the future-proofed projector delivers an eye-pleasing visual experience.

Install and forget - requiring zero maintenance over its long 20,000 hour life, the completely sealed optical engine and laser light source means filter and lamp replacement is obsolete; paired with a minimal power consumption of just 357W in normal mode, the P605UL ensures low operational costs.

With optional WiFi and embedded MultiPresenter function for wireless presentation and screen sharing, this is the ideal meeting room and classroom tool, but also meets the needs of rental and staging companies and digital signage use cases.

Benefits

No filter service required - a completely sealed optical laser LCD engine allows a filter-free design. Brilliant colour brightness is maintained and servicing costs need no longer feature in your budget.

Low Noise Level - with 19dB*, the silent technology will not disturb your meeting.

Future-proof input management - thanks to 4K@30 Hz input processing.

Minimised Carbon Footprint - with only 357W power consumption in normal mode for lowering your TCO.

No lamp replacement - up to 20,000 h maintenance free operation possible due to Laser Light Source.

Risk Group 2 saves you installation and operation effort - because of the Risk Group 2 compliance, no prescribed safety precautions are necessary.

Professional and Flexible Installation - versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.

Product Information

| | |
|---------------|-----------------|
| Product Name | P605UL |
| Product Group | Laser Projector |
| Order Code | 60004811 |

Image

| | |
|--------------------------------------|---|
| Projection Technology | 3LCD Technology |
| Native Resolution | 1920 x 1200 (WUXGA) |
| Aspect Ratio | 16:10 |
| Contrast Ratio ¹ | 500000:1 |
| Brightness ¹ | 6000 ANSI Lumen (approx. 60% in Eco Mode) |
| Lamp | Laser Light Source |
| Lamp Life [hrs] | 20000 ² |
| Lens | F= 1.5-2.1, f= 17.2-27.6 mm |
| Lens shift | H:±29, V:+60,-0 |
| Keystone correction | +/- 30° manual horizontal / +/- 30° manual vertical |
| Projection Factor | 1.23 - 2 : 1 |
| Projection Distance [m] | 0.8 - 13.5 |
| Screen Size (diagonal) [cm] / [inch] | Maximum: 762 / 300"; Minimum: 76.2 / 30" |
| Zoom | Manual; x1.6 |
| Focus Adjustment | Manual |
| Supported Resolutions | 3840x2160 @ 30hz digital; 3840 x 2160 (Maximum resolution of digital input); 1920x1200 (Maximum resolution of analog input) |

Connectivity

| | |
|---------------|--|
| RGB (analog) | Input: 1 x Mini D-sub 15 pin |
| Digital | Input: 1 x HDBaseT; 2 x HDMI™ supporting HDCP |
| Audio | Input: 1 x 3.5 mm Stereo Mini Jack for Computer analog; 2 x HDMI audio Output: 1 x 3.5 mm Stereo Mini Jack (variable) |
| Control | Input: 1 x D-Sub 9 pin (RS-232) (male) |
| LAN | 1 x RJ45; Optional WLAN |
| USB | 1 x Type B (for Service); 1x Type A (USB 2.0 high speed) with 2.0A Power Supply |
| Video Signals | NTSC 3.58; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM |

Remote Control

| | |
|----------------|---|
| Remote Control | Aspect Ratio; Audio Control; Auto Adjust; Eco Mode Control; Freeze-function; Help-function; ID set; Keystone Correction; Magnify-function; Page (up, down); Picture Adjust; Picture Mute; Power (On-OFF); Presentation and Mouse Control; Select (up, down, left, right); Source Select |
|----------------|---|

Electrical

| | |
|-----------------------|--|
| Power Supply | 100-240 V AC; 50 - 60 Hz |
| Power Consumption [W] | 357 (Normal) / 257 (Eco) / 1.6 (Network Stand-by) / 0.3 (Stand-by) |

Mechanical

| | |
|-----------------------------|---|
| Dimensions (W x H x D) [mm] | 480 x 122 x 407 (without lens and feet) |
| Weight [kg] | 9.7 |
| Fan Noise [dB (A)] | 19 / 25 / 28 (ECO / Normal / High Bright) |
| Colour Versions | White |

Environmental Conditions

| | |
|----------------------------|-----------|
| Operating Temperature [°C] | 5 to 40 |
| Operating Humidity [%] | 20 to 80 |
| Storage Temperature [°C] | -10 to 50 |
| Storage Humidity [%] | 20 to 80 |

Ergonomics

| | |
|-----------------------|--|
| Safety and Ergonomics | CE; EAC; ErP; RoHS; TUEV Type Approved; TÜV GS |
| Speakers [W] | 1 x 20 (mono) |

Additional Features

| | |
|-------------------------|---|
| Special Characteristics | Auto Power ON/OFF; Carbon Savings Meter; Constant Brightness Mode; Control ID Function; DICOM Simulation; Direct Power-Off Function; Free Tilt; Help Function; HTTP Browser Control; Kensington security slot; Keypad Lock; Light Source Adjustment; Magnify; Mouse Control with USB Display; MultiPresenter Function; NaViSet Administrator 2; Optional User Logo; OSD with 30 languages; Password Security System; Plug&Play W-LAN Option; Portrait Setting; Quick Start; Source Select with Beep Function; Test Pattern; Unique Power Saving Functions; USB Viewer; Virtual Remote for direct PC control |
|-------------------------|---|

Green Features

| | |
|----------------------|-------------------------------------|
| Ecological Materials | Downloadable manuals; ECO packaging |
| Ecological Standards | ErP compliant; RoHs compliant |

Warranty

| | |
|--------------|--|
| Projectors | 3 years pan-European service |
| Light Source | 3 years or 10000h (whatever comes first) |

Shipping Content

| | |
|-------------------|---|
| Shipping Contents | 2x AAA Batteries; IR Remote Control (477E); Mini D-SUB Signal Cable (1.8 m); Power Cord (1.8 m); Projector; Quick Setup Guide; Security Sticker; Users Manual; Utility software |
|-------------------|---|

Optional Accessories

| | |
|----------------------|--|
| Optional Accessories | Universal Ceiling Mounts (PJ01UCM, PJ02UCMPF); Wireless LAN module (NP05LM2; NP05LM4; NP05LM5) |
|----------------------|--|

¹ Compliance with ISO21118-2012

² 50% of initial brightness at the end of specified laser life time at 25 degree ambient temperature.



TUEV Type
Approved



CE



ErP



RoHS



TÜV GS

This product has been equipped with a laser module and is classified as Class1 of IEC60825-1 Ed3 2014 and is classified as RG2 of IEC62471-5 Ed1 2015.

DO NOT LOOK DIRECTLY INTO THE BEAM.

This document is © 2019 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 06.12.2019